Specification

Max. ¢80 mm

BL-440T

is servo type automatic double lacing machine with coil clamp device and auto thread cutting device.
And It has the knotting & suction device

And It has the knotting & suction device
for removal extra thread remained after
lacing.



	Stator outer diameter	Max. ¢150 mm
	Stator stack height	Standard height : 20 - 120 mm
	Coil end height	Max. 40 mm
	Process	4Station Turn table type (by AC Servo motor) 1st station : Stator load/unload 3rd station : End coil lacing & cutting 4th station : knotting
	Coil end lacing	Diamond binding & double needle type
	Driving	AC Geared motor with inverter
	Needle up/down & back/forward	Cam & Link
	Needle Twist	AC Servo Motors

Description

Stator inner diameter

Mouse movement

Stack height



Operation

Dimension

Weight

Machine Feature

Working

Range

- ctaron mongrit	ragaetea ay res corre meter
Stator index	AC Servo motor
Thread Holding & Cutting	Heater
Automatic Knotting device	With Suction device & Heater
Coil & Core clamp	Upper clamp by Air cylinder
Tension unit	Spring type
Control & operation	Motion control & Touch screen
Stator load/unload	Manual
Length . Width .height	1900 x 1270 x 1800 mm

About 1200kg

Link type

Adjusted by AC Servo motor